

# KBI® Engine Starting Solutions

## KrinkingKART JR.™ Jump-Start Carts

### Powered By **KAPower**® Supercapacitors

- 30 Second Charge Provides **FULL** Cranking Power
- **NEVER** Needs To Be Plugged Into An A/C Power Source
- No **Lead-Acid** Batteries To Maintain Or Replace

### Always Ready

- Delivers up to **3000** Amps of Cranking Power
- Can Be Re-Charged Over **1,000,000** Times
- Power Output Is Virtually Unaffected By Temperatures

### Revolutionary Design

- Capacitor Is Sealed, **No Maintenance** Required
- Built In **Safe-Guards**
  - Remote Power Button
  - Reverse Polarity Lockout Protection

**Heavy Duty  
Jump-Start Cart  
Giving An Engine  
The Power It  
Needs To Start.**



Easily Portable: Only 37 lbs.

KBI'S KRINKINGKART JR. CAN BE RECHARGED FROM MOST ANY CRANKING BATTERY, EVEN THE "RUN-DOWN" BATTERY ON THE VEHICLE THAT IS ABOUT TO BE JUMP-STARTED.



The heart of the KrinkingKART JR. is the KAPower supercapacitor. The KAPower supercapacitor is initially energized from the vehicle's electrical system. KAPower then stores the energy until needed. KAPower has a long service life upwards of 1,000,000 cycles and can outlast the vehicle it is jump-starting. The KAPower is virtually unaffected by temperatures and is maintenance free.



|  | Kranking-KART Mini™ | Kranking-KART Jr.™ | Kranking-KART Jr.™ | Kranking-KART Jr.™ Combination |
|--|---------------------|--------------------|--------------------|--------------------------------|
|--|---------------------|--------------------|--------------------|--------------------------------|

**Specifications**

|                    |         |          |          |            |
|--------------------|---------|----------|----------|------------|
| Voltage            | 12 Volt | 12 Volt  | 24 Volt  | 12/24 Volt |
| Engines Size Up To | 8 Liter | 15 Liter | 18 Liter | 18 Liter   |
| Cable Length       | 7 Feet  | 7 Feet   | 7 Feet   | 7 Feet     |
| Cable Gauge        | 4 GA    | 2/0      | 2/0      | 2/0        |

**Dimensions and Weight**

|                        |                     |                 |                 |                 |
|------------------------|---------------------|-----------------|-----------------|-----------------|
| Dimensions (L x W x H) | 14" x 6.5" x 11.75" | 20" x 12" x 17" | 20" x 12" x 17" | 20" x 12" x 17" |
| Weight                 | 19 lb               | 37 lb           | 37 lb           | 52 lb           |

\* Models maybe customized per customers specifications.

\*\* Military models will contain NATO connectors or a combination of NATO and HD Booster clamp connectors.